

# Installation instruction

**PrimaCover Protection board**

Article no.:

**900092**

Covering cardboard for universal use

- ◆ Anti-slip upper side
- ◆ Neutral execution, without imprint
- ◆ Without plastic coating, 100% recyclable

**Application range**

- ◆ For covering flat, hard surfaces when working indoors, protects the substrate from mechanical damage and moisture.
- ◆ Not suitable for porous surfaces.
- ◆ Not suitable for wet or freshly laid floors. Risk of waterlogging and associated negative changes to the floor.

**Installation instruction**

- ◆ The substrate must be clean, dry, pressure-resistant, dust- and grease free.
- ◆ Existing floor heating must be switched off.
- ◆ Lay the covering cardboard on the floor and fix the edges and corners with a suitable tape.
- ◆ Cut the covering cardboard at edges and corners with a safety knife.
- ◆ Do not lay over cables, protruding objects or other elevations, trip hazard!
- ◆ When laying several sheets next to each other, allow them to overlap by 10cm, press firmly and, if necessary, fix with a suitable tape.
- ◆ Check the surface of the board regularly and clean if necessary
- ◆ If the covering cardboard is damaged, remove it and lay out a new one, this is the only way to ensure reliable protection of the substrate.

**Re-usability**

- ◆ Remove impurities from the dry cardboard covering before rewinding.
- ◆ Before re-use, check the underside for dirt and remove if necessary.

**Note**

- ◆ Test the suitability of the product in advance in an inconspicuous place.
- ◆ No acceptance of liability for incorrect usage.
- ◆ It is absolutely necessary to pay attention to the installation instructions and application range!
- ◆ Always store in a dry place!
- ◆ 3 Months after installation, the non-woven should be removed from the surface. It is recommended to protect the non-woven from high temperatures and strong direct sunlight, as this could affect its technical characteristics.

**Disposal**

The non-woven can be disposed of in landfills after use, with dried paint or plaster residues, in compliance with official regulations.