

Installation instruction

PrimaCover Combi Article no.: 900047

Lightweight absorbent spun-bonded fabric with a strong liquid-proof film underneath; diffusion-closed

- ♦ Liquid-proof
- ♦ Resistant to wear and tearing
- ♦ Absorbent



T: +31 416 820 248

E: info@primaverde.nl

W: www.primaverde.nl

Application range

- ◆ For covering flat, hard surfaces when working indoors, protects the substrate from mechanical damager and moisture.
- ♦ Not suitable for porous surfaces.
- ♦ Not suitable for wet or freshly laid floors. Risk of waterlogging and associated negative changes to the floor.

Installation instruction

- ♦ The substrate must be clean, dry, pressure-resistant, dust- and grease free.
- ♦ Existing floor heating must be switched off.
- ♦ Lay the non-woven on the floor and fix the edges and corners with a suitable tape.
- ♦ Cut the non-woven at edges and corners with a safety knife.
- ♦ Don not lay over cables, protruding objects or other elevations, trip hazard!
- ♦ When laying several sheets next to each other, allow them to overlap by 10cm, press firmly and, if necessary, fix with a suitable tape.
- ♦ Check the surface of the board regularly and clean if necessary
- ♦ If the non-woven is damaged, remove it and lay out new fleece, this is the only way to ensure reliable protection of the substrate.

Re-usability

- ♦ Test the suitability of the product in advance in an inconspicuous place.
- ♦ Before re-use, check the underside for dirt and remove if necessary.

Note

- ◆ Test the suitability of the product in advance.
- ♦ No acceptance of liability for incorrect usage.
- ♦ It is absolutely necessary to pay attention to the installation instructions and application range!
- ♦ Always store in a dry place!
- ♦ 3 Months after installation, the non-woven should be removed from the surface. It is recommended to protect the non-woven from high temperatures and strong direct sunlight, as this could affect its technical characteristics.

Disposal

The non-woven can de disposed of in landfills after use, with dried paint or plaster residues, in compliance with official regulations.