


## Installation instruction

**PrimaCover Defend**

Article no:

900029, 900761

**Application range**

- ◆ Felt floor covering suitable for in- and outdoor hard surfaces, for flat precast concrete elements; for textile floor coverings, for all flat surfaces walkable by craftsmen.
- ◆ Vapour permeable, suitable for damp surfaces such as natural stone, parquet, wooden floor boards, ceramic tiles, etc.
- ◆ Available in rolls (25x1m) and as individual panels (80x120cm)

**Installation instruction**

- ◆ The surface must be clean, dry, pressure-resistant, dust- and grease free.
- ◆ Existing floor heating must be switched off.
- ◆ Lay the panels side by side or lay the felt roll tightly on the floor, do not let them overlap.
- ◆ Fix the edges and corners with suitable tape.
- ◆ The felt floor covering can be cut to size with a safety knife.
- ◆ Do not lay over cables, protruding objects or other elevations, trip hazard!
- ◆ When laying several lanes next to each other, do not let them overlap and fix them with a suitable tape if necessary.
- ◆ Check the surface of the covering regularly and clean if necessary.

**Re-usability**

- ◆ Remove dust, sand and stones.
- ◆ Pay attention to personal protection from dust when cleaning the board.
- ◆ The felt floor covering must be dry before re-laying.
- ◆ Before re-use, check the underside for dirt and remove if necessary.
- ◆ For sensitive surfaces it is recommended to use a new felt floor covering.

**Note**

- ◆ Test the suitability of the product in advance.
- ◆ No acceptance of liability for incorrect usage.
- ◆ It is absolutely necessary to pay attention to the installation instructions and application range.
- ◆ Always store in a dry place.

**Disposal**

Felt floor covering can be disposed of in landfills after use, in compliance with official regulations.