

# Installation instruction

**PrimaCover Synthetic**

Article nr.:

900813

## Application range

- ◆ For covering hard synthetic floors, protects the surface from mechanical damage and moisture.
- ◆ Not suitable for stairs.
- ◆ Not suitable for porous surfaces.
- ◆ Not suitable for wet or freshly laid floors. Risk of waterlogging and associated negative changes to the floor.

## Installation instruction

- ◆ The surface must be clean, dry, pressure-resistant, dust- and grease free.
- ◆ Existing floor heating must be switched off.
- ◆ Lay the fleece on the floor with the self-adhesive side facing downwards, without wrinkles and press down firmly..
- ◆ Cut the fleece at edges and corners with a safety knife.
- ◆ Do not lay over cables, objects or other elevations, trip hazard!
- ◆ When laying several lanes next to each other, allow them to overlap by 10cm, press firmly and if necessary, fix with a suitable tape.

## Re-usability

- ◆ Remove dirt etc. from the dry fleece before rewinding.
- ◆ Fold the fleece with the sticky side on top of each other, then rewind.
- ◆ Before re-use, check the underside for dirt and remove if necessary.

## Note

- ◆ Test the suitability of the product in advance.
- ◆ No acceptance of liability for incorrect usage.
- ◆ It is absolutely necessary to pay attention to the installation instructions and application range!
- ◆ Always store in a dry place!
- ◆ 3 Months after installation, the fleece should be removed from the surface. It is recommended to protect the fleece from high temperatures and strong direct sunlight, as this could affect its technical characteristics.

## Disposal

The fleece can be disposed of in landfills after use, with dried paint or plaster residues, in compliance with official regulations.