

Installation instruction

PrimaCover Carpet FR

Article nr.:

900931**Application range**

- ◆ For covering carpet flooring, protects the substrate from mechanical damage and moisture.
- ◆ Also suitable for stairs.
- ◆ Not suitable for porous surfaces.
- ◆ Not suitable for wet or freshly laid floors. Risk of waterlogging and associated negative changes to the floor.

Installation instruction

- ◆ The surface must be clean, dry, pressure-resistant, dust- and grease free.
- ◆ Existing floor heating must be switched off.
- ◆ The film must be applied without wrinkles and without excessive tension.
- ◆ Cut the film at edges and corners with a safety knife.
- ◆ Do not lay over cables, objects or other elevations, trip hazard!
- ◆ When laying several lanes next to each other, allow them to overlap by 5cm, press firmly and if necessary, fix with a suitable tape.

Note

- ◆ Test the suitability of the product in advance.
- ◆ No acceptance of liability for incorrect usage.
- ◆ It is absolutely necessary to pay attention to the installation instructions and application range!
- ◆ Always store in a dry place!
- ◆ 4 weeks after installation, the film should be removed from the surface. It is recommended to protect the film from high temperatures and strong direct sunlight, as this could affect its technical characteristics.

Disposal

The film can be disposed of in landfills after use, with dried paint or plaster residues, in compliance with official regulations.