

Installation instruction

PrimaCover Evapo

Article nr.:

900039, 900040, 900990**Application range**

- ◆ For covering freshly laid surfaces and/or treated ceramic tiles and wooden floors, protects the substrate from mechanical damager and moisture.
- ◆ Suitable for stairs.
- ◆ Especially for wet or freshly laid floors.

Installation instruction

- ◆ The surface must be clean, dry, pressure-resistant, dust- and grease free.
- ◆ Existing floor heating must be switched off.
- ◆ Lay the fleece on the floor with the self-adhesive side facing downwards, without wrinkles and press down firmly..
- ◆ Cut the fleece at edges and corners with a safety knife.
- ◆ Do not lay over cables, objects or other elevations, trip hazard!
- ◆ When laying several lanes next to each other, allow them to overlap by 10cm, press firmly and if necessary, fix with a suitable tape.

Special feature for installation on stairs

- ◆ Lay out the fleece at the top step far enough (approx. 50cm) and fix the beginning with adhesive tape to the surface.
- ◆ Lay out the fleece step by step in one go from top to bottom along the shape of the stairs, pressing the fleece on each step (tread and riser) without wrinkles.
- ◆ No moving pieces on the stairs, with exception of the spiral staircase.
- ◆ Lay the fleece on the lowest step far enough into the room and fix it.
- ◆ Regularly check the adhesion of the fleece to the surface.
- ◆ Check the surface of the fleece regularly and clean if necessary.
- ◆ If the fleece is damaged, remove and lay out new fleece, this is the only way to ensure reliable protection of the surface.

Re-usability

- ◆ Remove dirt etc. from the dry fleece before rewinding.
- ◆ Fold the fleece with the sticky side on top of each other, then rewind.
- ◆ Before re-use, check the underside for dirt and remove if necessary.

Note

- ◆ Test the suitability of the product in advance.
- ◆ No acceptance of liability for incorrect usage.
- ◆ It is absolutely necessary to pay attention to the installation instructions and application range!
- ◆ Always store in a dry place!
- ◆ 3 Months after installation, the fleece should be removed from the surface. It is recommended to protect the fleece from high temperatures and strong direct sunlight, as this could affect its technical characteristics.

Disposal

The fleece can be disposed of in landfills after use, with dried paint or plaster residues, in compliance with official regulations.