

PrimaCover Defend

Nonwoven felt



Thick nonwoven felt in rolls and as individual panels. For maximum protection of various surfaces. Prevents mechanical damage caused by debris, point loads, rollers, etc.

Technical data (*)



Vapour-open



Extra robust



Anti-slip

Composition

Material

100 % recycling fibres

Technical data

Dimensions
Thickness
Colour

Fiber board

80 x 120 cm
approx. 4 mm.
Gray-multicoloured

Roll

1 m x 25 m
approx. 4 mm.
Gray-multicoloured

Properties

100% vapour-open, hence suitable for damp surfaces, natural stone and parquet
Simple to adapt
Very effective mechanical protective effect, even with point loads
Re-usable
Practically lint-free

Application

Suitable for almost all surfaces, including natural stone and parquet

Processing

In case of heavy loads, fix the edges with a suitable tape. For example, PrimaCover Standard or PrimaCover Active can be applied underneath for a liquid proof protection.

Comments

Test the suitability of the product in advance.

We are unable to supervise the proper and therefore successful processing of the products. Therefore, we can only guarantee the quality of the products, but not of their processing.

The details stated above are guideline values established in our laboratories and at external test institutes. They may deviate slightly due to variations in the testing equipment. Subject to change without notice.

* following the respective standard