

Technical data sheet

Product: PrimaCover Glass PRIMACOVER.

900020	900578	900611
8719439000209	8719439005785	8719439006119
100m	100m	100m
0.5m	1m	0.5m
Blue-transparent	Colourless	Blue-transparent
	8719439000209 100m 0.5m	8719439000209 8719439005785 100m 100m 0.5m 1m

Technical data

Material	:	LDPE (polyethylene)	
Thickness	:	50 μm +/- 10%	
Density	:	0,922	
Weight per m²	:	46 gr +/- 10%	
Adhesive	:	Acrylic	
Elongation at break (%)			
MD	:	> 200%	
CD	:	> 400%	
Adhesive strength on glass	:	> 80cN/cm	AFERA 4001

Usage

The film must be applied to dry and clean surfaces.

The application must be done without grease, water or excessive stretching of the film.

The film must be removed again within 4 weeks.

Application

Glass protection film for indoor and outdoor use.

Storage

Temperature between +10°C and +30°C.

Relative humidity: 50%

6 months in original packaging. The film must be processed during this time.

Proper and thus successful processing of the product is not within our control. A guarantee can therefore only be given for the quality of the product and not for its processing. It is the responsibility of the user to determine the suitability of our products for their purpose.

The above data are approximate values obtained in our laboratories and at external testing institutes. They may also show slight deviations due to variations in test equipment.

The right to make changes without prior notice is reserved.