

## **PrimaCover Interior**

## Self-adhesive film with fleece layer (hard surfaces)

PrimaCover Interior consists of a strong, self-adhesive, waterproof film with a protective non-woven layer on top.

Technical data (*)					
	Protects aga mechanical c		Absorbent		Liquid-proof
	For floors an	d stairs		1 million	Anti-slip
Composition		Upper side Carrier Adhesive	Polyester LDPE film Acrylate dispersion		
Dimensions		Rolls	1 m x 25 m		
Technical o	data	Colour Fleece thickness Film thickness	White 200 g/m² 35 μm		
Properties		Anti-slip Self-adhesive Absorbent Protects against mechanical damage Liquid-proof Easy to use			
Application		For hard surfaces Suitable for horizontal and vertical surfaces Suitable for floors and stairs			
Processing		Lanes overlap by approx. 10 cm, press seams well			
Comments		Lay on thoroughly dried substrates. Test the suitability of the product in advance. Switch off underfloor heating before use. Remove within 3 months after installing			

We are unable to supervise the proper and therefore successful processing of the products. Therefore, we can only guarantee the quality of the products, but not of their processing.

It is up to the user to check the suitability of our products for the intended purpose.

The details stated above are guideline values established in our laboratories and at external test institutes. They may deviate slightly due to variations in the testing equipment. Subject to change without notice.

\* following the respective standard

Primaverde BV Industrieweg 22a NL-5145PV Waalwijk